

Router Donyx RS52 5G RedCap

Industrial single-module NR5 (RedCap) router with Wi-Fi, GPI/GPO, support for PoE IN and PoE OUT



The RS52 5G RedCap is a compact industrial router designed for reliable data transmission over cellular networks using 5G NR (New Radio) and LTE technologies.

Equipped with an NR5 RedCap module, the router provides data transfer speeds of up to 220 Mbps (downlink) and 120 Mbps (uplink). RedCap benefits from the improved spectrum efficiency and reduced latency of 5G, making it suitable for demanding applications requiring high performance in real-world scenarios.

The RS52 5G RedCap features industrial-grade interfaces, including GPI/GPO, PoE IN, and PoE OUT, to support a wide range of connectivity requirements in industrial environments. Additionally, it includes an integrated Wi-Fi access point supporting IEEE 802.11b/g/n standards, enabling wireless network deployment.

At the core of the RS52 5G RedCap is a high-performance MIPS processor, ensuring reliable operation and efficient handling of networking tasks. The router runs on a customized firmware based on OpenWRT version 19, an open-source platform that enables flexible functionality and regular updates. This adaptability allows the RS52 5G RedCap to meet diverse application needs, from simple connectivity to advanced network configurations.

Data transmission is secured with robust encryption protocols, ensuring the safety and integrity of transmitted information.

The RS52 5G RedCap supports a comprehensive suite of network functions, including: DNS and Dynamic DNS (DynDNS), SSH Server, TFTP Client and Wget, SNMP, DHCP Server, Firewall and NAT, NTP Client, VLAN support.

Designed for both wireless and wired connectivity, the RS52 5G RedCap is ideal for use cases such as:

- Payment terminals and ATMs
- Industrial equipment nodes
- Mobile offices
- Security and video surveillance systems
- Monitoring and control systems
- Other applications requiring fast, reliable Internet access



Communication Standards

- 5G NR (New Radio) and LTE technologies, SMS

Electrical Specifications

- Supported Power Supply Voltage: 9–54 V DC
- Current consumption, maximum:
 - At power supply voltage +12 V – 800 mA
 - At power supply voltage +24 V – 400 mA

Physical Specifications

- Maximum dimensions (including connectors): 130 × 95 × 35 mm
- Maximum weight: 240 g
- Enclosure Material: Aluminum
- Enclosure Protection Rating: IP30
- Operating Temperature Range: from -40°C to +65°C
- Storage Temperature Range: from -40 to 50°C
- Operating Humidity: from 10 to 80% noncondensing

PoE Characteristics

When operating with Power over Ethernet (PoE), the supply voltage of the device must be at least 12V.

- Passive PoE-IN available on **Port 1**. Supported Passive PoE-IN voltage range : 9–54 V
- Passive PoE-OUT available on **Port 2**. Supported Passive PoE-OUT voltage range: 11–53 V
- Maximum load current for Passive PoE-OUT:
 - At supply voltage +12 V: 800 mA
 - At supply voltage +24 V: 500 mA

Network Functions

Routing	Static and dynamic routing (OSPFv2, BGP)
Network Protocols	PPP, PPPoE, IPoE (Static, DHCP Client), TCP, UDP, ARP, IPv4, ICMP, HTTP, HTTPS, TLS, SSL
Connection Monitoring	Ping Reboot, Periodic Reboot, LCP and ICMP for link tracking
Firewall	Port forwarding, ZONE-based rules, NAT helpers (H.323, SIP-alg, etc), pre-configured firewall rules, custom rules
DHCP	Static and dynamic IP address allocation, DHCP Relay, Relayd
DDNS	Quick settings for major providers and manual setup options for others
Network Backup	VRRP; Wired, Mobile, or WiFi WAN. Supports automatic failover to an alternative connection (Automatic Failover)
Network Services	DHCP Server, NTP, DNS, VRRP, SSH, UPnP, SNMP, Telnet Client, SMTP

Tunneling

OpenVPN	Ability to run multiple clients and servers simultaneously
OpenVPN	Encryption: AES-128-CBC, AES-192-CBC, AES-256-CBC
IPsec	IKEv1, IKEv2. Supported encryption algorithms: 3DES, AES128, AES192, AES256
GRE	GRE TUN (Layer 3), GRE TAP (Layer 2)
EoIP	MikroTik RouterOS protocol based on GRE RFC 1701
PPTP, L2TP	Client mode support for L2TPv2, L2TPv3
DMVPN	Client mode operation, additional IP Security encryption

Security Features

Authentication	Pre-shared key, digital certificates, X.509 certificates
Firewall	Pre-configured firewall rules (managed via Web), unlimited firewall configuration; DMZ; NAT; NAT-T

Attack prevention	DDOS prevention (SYN flood protection, SSH attack prevention, HTTP/HTTPS attack prevention), port scan prevention (SYN-FIN, SYN-RST, X-mas, NULL flags, FIN scan attacks)
-------------------	---

VLAN	Port and tag based VLAN separation
------	------------------------------------

Access control	WiFi access control (MAC address filter)
----------------	--

Hardware Specifications

Number of Cellular Modules	1 x NR5 (RedCap)
----------------------------	------------------

Processor	MIPS 24KEc 580 MHz
-----------	--------------------

Dynamic RAM	128 MB
-------------	--------

Flash Memory Capacity	32 MB
-----------------------	-------

Wi-Fi	2.4 GHz 802.11b/g/n
-------	---------------------


Ports and Connectors

Microfit4 Connector	Power, GPI/GPO
---------------------	----------------

Ethernet Ports	2 x 10/100 Mbps
----------------	-----------------

SIM Card Slots	2 x Mini SIM
----------------	--------------

RST Button	Reset Button
------------	--------------

 Specifications may change without prior notice!