

Router Donyx RX54x2 5G RedCap

Industrial router
with dual 5G NR (RedCap) Module Support,
Wi-Fi



This industrial-grade 5G router supports 5G NR (New Radio), delivering download speeds of up to 220 Mbps and upload speeds of up to 120 Mbps per module. With dual modules, the router ensures resilient connectivity through automatic failover and load balancing, providing seamless operation and minimizing downtime. Dual-SIM functionality ensures connection redundancy and allows for scheduled operation.

The router offers a comprehensive range of wired and wireless connectivity options. These include an integrated 802.11b/g/n Wi-Fi access point, four 10/100/1000 Ethernet ports, RS-232 and RS-485 serial interfaces, and seven configurable GPIO pins offering maximum flexibility for integration with external devices.

Powered by a high-performance MIPS processor, the router runs custom firmware based on OpenWRT 19. This open-source platform allows for customization and future feature enhancements. Robust security is provided through advanced encryption protocols and a comprehensive firewall.

The router supports a full suite of networking features, including NAT, DHCP, DNS, DynDNS, SSH, TFTP, Wget, SNMP, VRRP, VLAN, NTP, and optional dynamic routing.

Designed for demanding industrial environments, the router features seamless WAN failover and a wide operating temperature range of -40°C to +65°C. This versatile connectivity solution is ideal for applications ranging from remote network connectivity and industrial control systems to secure data transmission for financial terminals and robust video surveillance deployments.



Communication Standards

- 5G NR (New Radio) and LTE technologies, SMS

Electrical Specifications

- Power supply voltage from 8 to 30 V (DC)
- Current consumption, maximum:
 - At power supply voltage +12 V – 1000 mA;
 - At power supply voltage +24 V – 500 mA;
- Passive PoE-IN available on **Port 1**. Supported Passive PoE-IN voltage range : 8-30 V

Physical Specifications

- Maximum dimensions (including connectors): 135 × 120 × 40 mm
- Maximum weight: 300 g
- Enclosure Material: Aluminum
- Enclosure Protection Rating: IP30
- Operating Temperature Range: from -40°C to +65°C
- Storage Temperature Range: from -40 to 50°C

Network Functions

Routing	Static and dynamic routing (OSPFv2, BGP)
Network Protocols	PPP, PPPoE, IPoE (Static, DHCP Client), TCP, UDP, ARP, IPv4, ICMP, HTTP, HTTPS, TLS, SSL
Connection Monitoring	Ping Reboot, Periodic Reboot, LCP and ICMP for link tracking
Firewall	Port forwarding, ZONE-based rules, NAT helpers (H.323, SIP-alg, etc), pre-configured firewall rules, custom rules
DHCP	Static and dynamic IP address allocation, DHCP Relay, Relayd
DDNS	Quick settings for major providers and manual setup options for others

Network Backup	VRRP; Wired, Mobile, or WiFi WAN. Supports automatic failover to an alternative connection (Automatic Failover)
----------------	---

Network Services	DHCP Server, NTP, DNS, VRRP, SSH, UPNP, SNMP, Telnet client, SMTP, NTRIP Client
------------------	---

Tunneling

OpenVPN	Ability to run multiple clients and servers simultaneously
---------	--

OpenVPN	Encryption: AES-128-CBC, AES-192-CBC, AES-256-CBC
---------	---

IPsec	IKEv1, IKEv2. Supported encryption algorithms: 3DES, AES128, AES192, AES256
-------	---

GRE	GRE TUN (Layer 3), GRE TAP (Layer 2)
-----	--------------------------------------

EoIP	MikroTik RouterOS protocol based on GRE RFC 1701
------	--

PPTP, L2TP	Client mode support for L2TPv2, L2TPv3
------------	--

DMVPN	Client mode operation, additional IP Security encryption
-------	--

Security Features

Authentication	Pre-shared key, digital certificates, X.509 certificates
----------------	--

Firewall	Pre-configured firewall rules (managed via Web), unlimited firewall configuration; DMZ; NAT; NAT-T
----------	--

Attack prevention	DDOS prevention (SYN flood protection, SSH attack prevention, HTTP/HTTPS attack prevention), port scan prevention (SYN-FIN, SYN-RST, X-mas, NULL flags, FIN scan attacks)
-------------------	---

VLAN	Port and tag based VLAN separation
------	------------------------------------


Access control	WiFi access control (MAC address filter)
----------------	--

Hardware Specifications

Number of Cellular Modules	2 x NR5 (RedCap)
Processor	MIPS 24KEc 580 Mhz
Dynamic RAM	128 MB
Flash Memory Capacity	32 MB
Wi-Fi	2,4 GHz (802.11b/g/n 2T2R MAC)
WiFi Transmit Power	up to 16 dBm (40 mW)

Ports and Connectors

Ethernet Connector	1 x 10/100 Mbps
Microfit4 Connector	Power
DB9 connector	RS232
Breakaway Terminal Connector	RS485, 7 x GPIO, power
Card slot	MicroSDHC
SIM Card Slots	Mini SIM
RST Button	Reset Button

 Specifications may change without prior notice!